

CEILING FAN HEATER

ASK SERIES

AIR CURTAIN™

HEATED FROM ABOVE, SOOTHING BELOW

The AIR CURTAIN™ ceiling fan heater silently beams down heat from above. This unique model is ideal for rooms where wall space is limited. In bathrooms, the AIR CURTAIN™ can be installed just outside the shower or bathtub. With its ceiling-recessed casing, the AIR CURTAIN™ is an excellent way to provide discreet air circulation. The result: uniform heating and air movement, and reduction in mirror and window fog. By adding a wall timer, you can use it on demand.



CEILING MOUNTED

IDEAL FOR ROOMS WITH LIMITED WALL SPACE

HEATING ON DEMAND

WALL TIMER (OPTIONAL)

COMPACT AND QUIET

IDEAL FOR:

BATHROOM, ENTRYWAY, CHILD DAY CARE CENTER,
ROOM WITH LIMITED WALL SPACE

COLORS

- standard: white, silica white
- optional: almond, black, textured charcoal, silver, clear anodized (paint), nickel, champagne, light bronze, dark brown (10% surcharge)

FINISH

epoxy-polyester powdercoat

MANUFACTURING

- 22-gauge steel cabinet and 20-gauge steel grille
- 1/4 in. deep front grille
- easy access for maintenance purposes (no screws)

THERMAL PROTECTION

thermal protection with automatic reset

ELEMENT

nichrome element produces instant heat

CONTROL

- built-in thermostat (optional)
- wall thermostat (not included) – the use of an electronic thermostat is strongly recommended
- 60-minute timer (optional)

INSTALLATION

- ceiling mounted (recommended height of 8 ft., maximum of 9 ft.)
- surface mounted with surface adapter (optional)
- recessed or surface mounted with adapter for suspended ceiling (optional)
- unit can be mounted parallel or perpendicular to ceiling beams
- approved to be recessed in mineral wool; for all other materials please verify with the manufacturer of the insulating product

ACCESSORIES

PRODUCT	DESCRIPTION
SKT1*	tamper-proof built-in thermostat [120 V-347 V] (grille must be removed to access this type of thermostat)
SKTBA*	adapter for suspended ceiling (2 ft. x 2 ft.) (recessed or surface mounted)
SKSA*	surface adapter (ASK model)
SKSAII*	surface adapter (ASKII model)
FD60MCW70	60-minute wall timer [120 V-277 V]

* Add W for white or SW for silica white
* Factory installed

TECHNICAL SPECIFICATIONS

PRODUCT	POWER	VOLTAGE	PHASE	FLOW	THROW DISTANCE		HEAT RISE		WEIGHT	
					M	FT.	°C	°F	KG	LB
ASK0501	500	120	1	60	2.4	8	26	46	5	11
ASK0508	500	208	1	60	2.4	8	26	46	5	11
ASK0502	500/375	240/208	1	60	2.4	8	26	46	5	11
ASKII0507	500	277	1	60	2.4	8	26	46	5	11
ASK0751	750	120	1	60	2.4	8	42	75	5	11
ASK0758	750	208	1	60	2.4	8	42	75	5	11
ASK0752	750/560	240/208	1	60	2.4	8	42	75	5	11
ASKII0757	750	277	1	60	2.4	8	42	75	5	11
ASK1001	1000	120	1	60	2.4	8	54	97	5	11
ASK1008	1000	208	1	60	2.4	8	54	97	5	11
ASK1002	1000/750	240/208	1	60	2.4	8	54	97	5	11
ASKII1007	1000	277	1	60	2.4	8	54	97	5	11
ASK1251	1250	120	1	60	2.4	8	79	143	5	11
ASK1258	1250	208	1	60	2.4	8	79	143	5	11
ASK1252	1250/940	240/208	1	60	2.4	8	79	143	5	11
ASKII1257	1250	277	1	60	2.4	8	79	143	5	11
ASK1501	1500	120	1	60	2.4	8	102	184	5	11
ASK1508	1500	208	1	60	2.4	8	102	184	5	11
ASK1502	1500/1125	240/208	1	60	2.4	8	102	184	5	11
ASKII1507	1500	277	1	60	2.4	8	102	184	5	11
---	2000	120	1	90	3.2	10'6"	109	196	5	11
---	2000	208	1	90	3.2	10'6"	109	196	5	11
ASK2002	2000/1500	240/208	1	90	3.2	10'6"	109	196	5	11
ASKII2007	2000	277	1	90	3.2	10'6"	109	196	5	11

Add W for white or SW for silica white (see page 8 for optional colors and contact your °STELPRO representative for all other colors)
 --- not available

TECHNICAL DRAWINGS

