



**Product Number:** 60108

**Order Abbreviation:** SLMFLD1A/100UNVD840/WF/BZ

**General Description:** Slim Floodlight 1A, 100 watts, 120-277V, 80+CRI, 4000K, wide flood distribution, bronze painted finish

#### Product Information

Power Factor	?0.90
Primary Lamp Type	SMD
Minimum Operating Temperature - Celsius	-40
Minimum Operating Temp - Fahrenheit	-40
Total Harmonic Distortion (THD)	< 20 %
Efficacy (LPW)	123
Abbrev. With Packaging Info.	SLMFLD1A100UNVD840WFBZ 1/CS 1/SKU
Color Temperature/CCT (K)	4000
Ordering Abbreviation	SLMFLD1A/100UNVD840/WF/BZ
Lumens	12300
Nominal Voltage (V)	120.00
UPC Code	UPC046135601088
Color Rendering Index (CRI)	80
Lumens (lm)	12300
Color Range	4000 K
Energy Star Rated	No
Fixture Warranty	5 years
Housing	Aluminum
Luminaire Finish	Bronze
Luminaire Type	Flood light
Maximum Operating Temperature-Celsius	40
Maximum Operating Temperature-Fahrenheit	104
Dimensions	12.4x2.4x14.8
Certification Listing	RoHS, FCC, cULus